

Product quality			
Formats		1285 x 194 x 8 mm	2200 x 235 x 8 mm
Packaging	Pack:	10 elements / 2,493 m ² / 16,69 kg	6 elements / 3.102 m ² / 20.87 kg
	Pallet:	40 packs / 99,72 m ² / 682,49 kg	39 packs / 120.98 m ² / 843.76 kg

Tolerances (Requirement EN 16511:2014)			
Squareness of the elements (≤ 0.50mm)		≤ 0,15 mm	
Determination of Linearity (≤ 0.30 mm/m)		≤ 0,20 mm/m	
Flatness concave / convex	lengthwise (≤ 0.50/≤ 1.0 %)	≤ 0,35/≤ 1,0 %	
	wide (≤ 0.10/≤ 0.15 %)	≤ 0,10/≤ 0,15 %	
Surface flushness	(average ≤ 0.15 mm)	(average ≤ 0.10 mm)	
	(max. ≤ 0.20 mm)	(max. ≤ 0.15 mm)	
Opening between installed elements	(average ≤ 0.15 mm)	(average ≤ 0.05 mm)	
	(max. ≤ 0.20 mm)	(max. ≤ 0.10 mm)	

Guarantee (according Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion (up to max. 20sqm)
Lifetime	10 Years	- cleaning an maintenance see instructions
		- technical changes reserved



Classification			
		Test method	Rating
	Utility class 23 domestic areas with intensive use	EN 16511	Living room, hall, kitchen, home office
	Utility class 33 commercial areas with intensive use	EN 16511	Classrooms, open-plan offices, shops
	Reaction to fire	EN 13501-1	C _{f1} s1
	Slip resistance	EN 13893 EN 14041	μ ≥ 0,50 DS
	Staining resistance	EN 438-2	Category 1 + 2: level 5, no visible change Category 3: level 4, slight change
	Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
	Resistance to roller castor chairs	EN 425	Type W, no visible changes
	Thermal resistance Suitable for installation over underfloor heating when using an appropriate moisture barrier.	EN 12667	0,075 m ² *K/W
	Moving a furniture leg	EN 424	No visible changes
	Indentation-residual	EN ISO 24343-1	≤ 0,05 mm
	Formaldehyde emission (E1 = 0.1 ppm)	ISO 16000	≤ 0,05 ppm
	Acoustical - Impact noise reduction	EN ISO 10140	16 dB (on PE film) 17 dB (on Akustik-Protect 100)
	Length- and Square separating force	ISO 24334	lengthwise ≥ 6 KN/m transversely ≥ 4 KN/m
	Abrasion	prEN 15468 Annex A	> 7.000 rev.
	Impact resistance	EN 13329 Annex F	≥ 1.800 mm
	Dimensional stability	EN 16511	≤ 0,25 %
	Micro scratch resistance	EN 16094	Method A MSR-A2 Method B MSR-B1
	Slip resistance on an inclined plane	DIN 51130	R10
	Disposal	EAK-Code-number	20 03 01
	Suitable for damp rooms: With up to four hours of protection in the case of standing water (please observe installation instructions).		

Changed:	QMB Parador	File:	20190201_PA_TDS_Modular-ONE_EN
Date:	01.01.2018	Latest update at:	www.parador.eu/service/catalogues-downloads/technical-data-sheets
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.03.2019