









Product quality									
Type	Decor skirtings					Decor- and Real wood skirtings			
	HL 1	HL 2	HL 3	Quad	SL 3	SL 2	SL 4	SL 6	SL 18
Length	2570	2570	2570	2570	2570	2570	2570	2570	2570
Width/Height x Thickness	65 x 19	85 x 19	105 x 19	14 x 20	40 x 16	50 x 19.5	60 x 19.5	50 x 16	70 x 16.5
Pieces per pack	15	10	8	70	25	36	32	20	15
Weight per piece	1.54 kg	2.26 kg	2.97 kg	0.40 kg	0.90 kg	1.00 kg	1.26 kg	1.30 kg	1.75 kg
Weight per carton	23.10 kg	22.60 kg	23.76 kg	28.00 kg	22.50 kg	36.00 kg	40.32 kg	26.00	26.25 kg
Colour of the clip	green	green	green	-	orange	green	red	blue	red

Product labelling					Tolerances (RAL-GZ 430)	
					Surface quality	fulfilled
					Milling	fulfilled
					Fit	fulfilled
					Workmanship	fulfilled

Functional / Surface quality (Test standard)			
		Test standard	Rating
	Chemical resistance	(DIN 68 861 T.1)	1 C
	Abrasion resistance	(DIN 68 861 T.2)	2 E
	Scratch resistance	(DIN 68 861 T.4)	4 E
	Light fastness	(DIN 53 387)	≥ 6
	Humid alternating atmosphere (DIN 50 016), RAL 430 1-2, 3 cycles	5h 23°C / 85% 14h 40°C / 92% 24h 23°C / 50%	Decor skirtings: fulfilled Real wood skirting: limited suitability for damp rooms
	Temperature resistance	(DIN 9242)	no visible changes
	Formaldehyde (E1 = 0,1 ppm)	EN 717-1	≤ 0,05 ppm
	Disposal		Private waste disposal with normal household waste / bulky waste possible

Changed:	QMB	File:	20161016_20161016_PA_TDS_Leisten_EN
Date:	01.01.2014	Updates at:	www.parador.de
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			16.10.2016